



FEATURES:

OIL RESISTANT PVC JACKET. MEETS RES I & II. UV RESISTANT.

APPLICATIONS:

DOMESTIC AND EXPORTED PORTABLE TOOLS, COMMERCIAL EQUIPMENT.

TECHNICAL DATA:

UL, CSA LISTED, <HAR> APPROVED. RoHS, CE SJTO, H05VV-F STRANDED COPPER CONDUCTORS, BLACK JACKET. NOMINAL VOLTAGE: 300V SJTO, 500V <HAR>, 600V AWM

TEMPERATURE: - 40C TO + 90C SJTO. -30C TO + 70C <HAR>

3 COND: BLUE, BROWN, GREEN/YELLOW.

4 COND: BROWN, BLACK, GRAY, GREEN/YELLOW.

5 COND: BLUE, BROWN, BLACK, GRAY, GREEN/YELLOW.

PART NUMBER	CONDUCTORS/AWG	NOMINAL O.D.	APPROX. WGT. LBS/MFT
311803	3-17AWG 1.0MM	0.300" (7.6mm)	53
311804	4-17AWG 1.0MM	0.330" (8.3mm)	73
311805	5-17AWG 1.0MM	0.375" (9.5mm)	93
311603	3-15AWG 1.5MM	0.332" (8.4mm)	73
311604	4-15AWG 1.5MM	0.364" (9.2mm)	84
311605	5-15AWG 1.5MM	0.405" (10.3mm)	100
311403	3-13AWG 2.5MM	0.407" (10.3mm)	102
311404	4-13AWG 2.5MM	0.447" (11.4mm)	130
311405	5-13AWG 2.5MM	0.496" (12.6mm)	150
105 DEGREE C “UNIVERSAL” SJTO CORDAGE			
1601318	3-17AWG 1.0MM	0.315" (7.9mm)	65
1601316	3-15AWG 1.5MM	0.360" (9.1mm)	82
1601314	3-14AWG 1.5MM	0.375" (9.5mm)	102
1601313	3-13AWG 2.5MM	0.406" (10.2mm)	117
1601312	3-11AWG 4.0MM	0.475" (12.0mm)	163