



FEATURES:

OIL, CHEMICAL, ABRASION RESISTANT NEOPRENE JACKET. UV RESISTANT, OUTDOOR USE.

APPLICATIONS:

DOMESTIC AND EXPORTED MACHINERY, COMMERCIAL EQUIPMENT, PORTABLE TOOLS.

TECHNICAL DATA:

UL, CSA LISTED, <HAR> APPROVED SOOW, H07RN-F. STRANDED COPPER CONDUCTORS.
NOMINAL VOLTAGE: 600V SOOW, 450/750V <HAR>. TEMP: -40C TO +90C SOOW. -25C TO +60C <HAR>
3 COND: BLUE, BROWN, GREEN/YELLOW. **4 COND:** BROWN, BLACK, GRAY, GREEN/YELLOW.
5 COND: BLUE, BROWN, BLACK, GRAY, GREEN/YELLOW.

PART NUMBER	CONDUCTORS/AWG/STRANDING	NOMINAL O.D.	APPROX. WGT. LBS/MFT
321803	3-18AWG (32/32) 1.00MM	.380 (9.6MM)	88
321404	4-14AWG (50/30) 2.50MM	.590 (15.1MM)	196
321405	5-14AWG (50/30) 2.50MM	.670 (16.9MM)	230
321204	4-12AWG (56/28) 4.0MM	.670 (17.0MM)	267
321205	5-12AWG (56/28) 4.0MM	.740 (18.7MM)	328
321003	3-10AWG (84/28) 6.0MM	.670 (16.9MM)	335
321004	4-10AWG (84/28) 6.0MM	.720 (18.2MM)	412
321005	5-10AWG (84/28) 6.0MM	.790 (20.1MM)	514
320803	3-8AWG (80/26) 10.0MM	.900 (22.9MM)	595
320804	4-8AWG (80/26) 10.0MM	.980 (25.0MM)	712