

**IEC 60309 DEVICES, IP44, IP67 (4H)  
2 Pole 3 Wire Grounding**  
30 Amp 120 Volt A.C. - North American Rated  
C(UL)US LISTED

Yellow Color



E-mail: [sales@internationalconfig.com](mailto:sales@internationalconfig.com)

Web site: [www.internationalconfig.com](http://www.internationalconfig.com)



DEVICE SPECIFICATION DOCUMENTS  
AVAILABLE ON OUR WEBSITE

**SPLASHPROOF IP44**

**WATERTIGHT IP67**

**Cable Mounting Plugs**

**888-21012-NS** Splashproof Plug, IP44 Rated.

**888-2168-NS** Watertight Plug, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon ( Polyamide 6 ) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-21012-NS



888-2168-NS

**Cable Mounting Connectors**

**888-31012-NS** Splashproof Connector, IP44 Rated.

**888-3168-NS** Watertight Connector, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon ( Polyamide 6 ) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-31012-NS



888-3168-NS

**Panel Mount Receptacles, Straight Type**

**888-13006-NS** Splashproof Receptacle, IP44 Rated.

**888-13023-NS** Watertight Receptacle, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-13006-NS



888-13023-NS

**Panel Mount Receptacles, Angled Type**

**888-1228-NS** Splashproof Receptacle, IP44 Rated.

**888-42324-NS** Watertight Receptacle, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-1228-NS



888-42324-NS

**Surface Mount Receptacles with Box**

**888-1113-NS** Splashproof Receptacle, IP44 Rated.

**888-1144-NS** Watertight Receptacle, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-1113-NS



888-1144-NS

**Surface Mount Inlets, Down Angled Type**

**888-631316** Splashproof Inlet, IP44 Rated.

**888-72324-NS** Watertight Inlet, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-631316



888-72324-NS

**Panel Mount Inlet, Straight Type**

**888-6234-NS** Splashproof Receptacle, IP44 Rated.

Nylon ( Polyamide 6 ) Body. Color: Yellow.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-6234-NS



999-623, 999-623-WP

**Plug and Inlet Closure Cap.**

**999-623** Color: Gray

**999-623-WP** Watertight Cap, IP67 Rated. Color: Gray



© 2014 International Configurations, Inc. Entire contents of this catalog copyrighted. [www.InternationalConfig.com](http://www.InternationalConfig.com)

International Configurations, Inc. • P.O. Box 3374 • Enfield, Connecticut 06083 • TEL (860) 749-6380 • FAX (860) 749-2985 171