

# IEC 60309 DEVICES, IP44, IP67 (6H)

## 4 Pole 5 Wire Grounding, 3 Phase

30 Amp 200-415 Volt A.C. - N. American Rated

32 Amp 220/380-240/415 Volt A.C. - European Rated

Red Color



E-mail: [sales@internationalconfig.com](mailto:sales@internationalconfig.com)

Web site: [www.internationalconfig.com](http://www.internationalconfig.com)

UNIVERSAL  
APPROVED



DEVICE SPECIFICATION DOCUMENTS  
AVAILABLE ON OUR WEBSITE

SPLASHPROOF IP44

WATERTIGHT IP67

### Cable Mounting Plugs

**888-231-NS** Splashproof Plug, IP44 Rated.

**888-2179-NS** Watertight Plug, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon ( Polyamide 6 ) Body. Color: Red.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-231-NS



888-2179-NS

### Cable Mounting Connectors

**888-331-NS** Splashproof Connector, IP44 Rated.

**888-3179-NS** Watertight Connector, IP67 Rated.

Compression Strain Relief & Cord Grip.

Nylon ( Polyamide 6 ) Body. Color: Red.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-331-NS



888-3179-NS

### Panel Mount Receptacles, Straight Type

**888-1333-NS** Splashproof Receptacle, IP44 Rated.

**888-1370-NS** Watertight Receptacle, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Red.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-1333-NS



888-1370-NS

### Panel Mount Receptacles, Angled Type

**888-1239-NS** Splashproof Receptacle, IP44 Rated.

**888-1288-NS** Watertight Receptacle, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Red.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-1239-NS



888-1288-NS

### Surface Mount Receptacles with Box

**888-103-NS** Splashproof Receptacle, IP44 Rated.

**888-1155-NS** Watertight Receptacle, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Red.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-103-NS



888-1155-NS

### Surface Mount Inlets, Down Angled Type

**888-2769-NS** Splashproof Inlet, IP44 Rated.

**888-27005-NS** Watertight Inlet, IP67 Rated.

Nylon ( Polyamide 6 ) Body. Color: Red.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C



888-2769-NS



888-27005-NS

### Panel Mount Inlet, Straight Type

**888-6256-NS** Splashproof Receptacle, IP44 Rated.

Nylon ( Polyamide 6 ) Body. Color: Red.

Contacts: Nickel Plated Brass, Brass.

Operating Temp: -25°C to + 80°C

### Plug and Inlet Closure Cap.

**999-625** Color: Gray

**999-625-WP** Watertight Cap, IP67 Rated. Color: Gray



888-6256-NS



999-625, 999-625-WP

