

CAT. No. 57311X1.0M	IEC 60320 C-14 POWER INLET, 15 AMPERE 250 VOLT, SNAP-IN PANEL MOUNT FOR 1.0 mm THICK PANEL, 6.3 x 0.8 mm (0.250" x 0.032") QUICK CONNECT Q.D. TERMINALS, 2 POLE-3 WIRE GROUNDING, IP30 RATED, BLACK.
-------------------------------	--

APPROVALS	C(RU)US <input checked="" type="checkbox"/> ENEC 10 <input checked="" type="checkbox"/> CCC <input checked="" type="checkbox"/> VDE <input checked="" type="checkbox"/>
CERTIFICATIONS	REACH <input checked="" type="checkbox"/> ROHS <input checked="" type="checkbox"/> ROHS2 (2011/65/EU) <input checked="" type="checkbox"/> ROHS3 (2015/863, 2017/2012) <input checked="" type="checkbox"/> CHINA ROHS <input checked="" type="checkbox"/> CE <input checked="" type="checkbox"/> UKCA <input checked="" type="checkbox"/>
STANDARDS	IEC 60320 C-14 <input checked="" type="checkbox"/> IEC 60320-1 <input checked="" type="checkbox"/> UL 60320-1 <input checked="" type="checkbox"/> CSA C22.2 No. 60320-1 <input checked="" type="checkbox"/>

DESCRIPTION:
 PANEL MOUNT: SNAP-IN MOUNTING FROM FRONT SIDE
 APPLIANCE INLET, PIN TEMPERATURE 70°C, PROTECTION CLASS I


ALL DIMENSIONS ARE IN MILLIMETERS

TECHNICAL DATA:

RATINGS IEC:	10A/250VAC; 50HZ
RATINGS UL/CSA:	15A/250VAC; 60HZ
DIELECTRIC STRENGTH:	>2KVAC BETWEEN L-N
	>2KVAC BETWEEN L/N-PE (1MIN/50HZ)
ALLOWABLE OPERATION TEMP:	-25°C TO +70°C
DEGREE OF PROTECTION:	FROM FRONT SIDE IP30 ACC TO IEC 60529
PROTECTION CLASS:	SUITABLE FOR APPLIANCES WITH PROTECTION CLASS I ACC TO IEC 61140
MATERIAL, HOUSING:	THERMOPLASTIC, BLACK, UL 94V-0

ADDITIONAL SIZES:

CATALOG No	DESCRIPTION
57311X1.2M	1.2mm THICK PANELS
57311	1.5mm THICK PANELS
57311X2.0M	2.0mm THICK PANELS
57311X2.5M	2.5mm THICK PANELS
57311X3.0M	3.0mm THICK PANELS



**IEC 60320 C-14
FRONT VIEW**

SIDE VIEW

**MOUNTING
DIMENSIONS**